

## **AMENDMENTS TO THE CLAIMS**

The following listing of claims will replace all prior versions and listings of claims in the application.

### **LISTING OF CLAIMS**

1. (Original) An elastic fastener comprising a hollow tubular portion, an internally threaded portion provided at one of the ends of said tubular portion, and a flange formed at the other end of said tubular portion,

wherein said tubular portion and said flange are integrally formed with each other and made of an elastomeric material selected from the group consisting of a styrene-based elastomer, a polyamide-based elastomer, a polyester-based elastomer, a urethane-based elastomer and an olefin-based elastomer, and

said internally threaded portion is formed of a rigid resin material selected from the group consisting of a polycarbonate resin, a styrene-based resin, an acrylic-based resin, a polyester-based resin, a nylon-based resin, a modified PPE resin and a polymer alloy composed of polycarbonate, said internally threaded portion having a nut shape, said internally threaded portion being integrally fixed to said tubular portion in a hole of said tubular portion.

2. (Original) An elastic fastener as defined in claim 1, wherein said elastomeric material of said flange and said tubular portion has a JIS-A hardness in the range of 40 to 90 degree.

3. (Original) An elastic fastener as defined in claim 1, wherein said flange and said tubular portion are integrally formed with each other by injection molding, said internally threaded portion being formed as a single piece by injection molding, and said internally threaded portion being joined to said tubular portion by fusion bonding.

4. (Original) An elastic fastener as defined in claim 2, wherein said flange and said tubular portion are integrally formed with each other by injection molding, said internally threaded portion being formed as a single piece by injection molding, and said internally threaded portion being joined to said tubular portion by fusion bonding.

5. (New) An elastic fastener comprising:  
a tubular portion defining a through bore, an internally threaded portion provided at a first end of said tubular portion, and a flange formed at a second end of said tubular portion,

wherein said tubular portion and said flange are monolithic component formed of a first polymer material, and

said internally threaded portion is formed of a second polymer material, said second polymer material being a rigid resin material, said internally threaded portion defining an external surface which is configured to be fixably coupled to the through bore.

6. (New) An elastic fastener as defined in claim 5, wherein said first material has a JIS-A hardness in the range of 40 to 90 degree.

7. (New) An elastic fastener as defined in claim 5, wherein said flange and said tubular portion are integrally formed with each other by injection molding, and wherein said internally threaded portion is formed as a single piece by injection molding, and said internally threaded portion is joined to said tubular portion by fusion bonding.

8. (New) An elastic fastener as defined in claim 6, wherein said flange and said tubular portion are integrally formed with each other by injection molding, said internally threaded portion being formed as a single piece by injection molding, and said internally threaded portion being joined to said tubular portion by fusion bonding.

9. (New) An elastic fastener as defined in claim 5 wherein said tubular portion and said flange are integrally formed with each other and made of an elastomeric material is selected from the group consisting of a styrene-based elastomer, a polyamide-based elastomer, a polyester-based elastomer, a urethane-based elastomer and an olefin-based elastomer.

10. (New) An elastic fastener as defined in claim 5 wherein said rigid resin material is selected from the group consisting of a polycarbonate resin, a styrene-based resin, an acrylic-based resin, a polyester-based resin, a nylon-based resin, a modified PPE resin and a polymer alloy composed of polycarbonate.